

Famochem rotary gear pumps designed for foam extinguishing system.-They are SelfPriming and can pump Multiple Viscosities of Foam or Water. This versatile design is suitable for Electric, PTO, Diesel/Gasoline Engine, Water Driven or Hydraulic drive motors.

**Design Features:**

- Timing Gears Synchronize the Two Pumping Rotors.
- Timing Gears Allow for DRY Running Without Damage.
- No Rotor Contact Allows for Pumping Foam or Water.
- Water Can Be Used for: Calibration, Testing and Training.

**Technical Data:**

Max Pressure: 2.0MPa | 20bar  
 Max Speed: 1800RPM  
 Viscosity : 9500cp max.[1]  
 Connection Diameter: DN80(88.9 O.D.)、 3”  
 Connection Type: Groove、 Thread、 Flange

[1]Brookfield viscometer, spindle #4, speed 30rpm.



**Materials :**

Pump body: Red Brass, ASTM B584 C83600  
 Rotor: Stainless Steel 17-4PH  
 Red Brass, ASTM B584 C83600  
 Liners: Red Brass, ASTM B584 C83600  
 Front Cover: Red Brass, ASTM B584 C83600  
 Back Cover: Red Brass ASTM B584 C83600  
 Timing Gear: Alloy Steel 20CrMnTi (ASTM A29M)  
 Lip Seal : FPM

**Performance -Water**

Foam Pump		1000rpm			1200rpm			1500rpm			1800rpm		
Pressure	Flow	Power	Torque	Flow	Power	Torque	Flow	Power	Torque	Flow	Power	Torque	
bar	L/min	kw	N.m	L/min	kw	N.m	L/min	kw	N.m	L/min	kw	N.m	
5.0	346	6	58	449	8	61	605	11	67	766	13	70	
6.9	318	8	73	421	10	76	579	13	81	739	16	87	
10.3	276	10	100	379	13	102	537	17	109	696	22	116	
13.8	242	13	127	344	16	130	501	21	137	662	27	144	
17.2	217	16	155	317	20	158	474	25	162	634	32	170	
20.0	202	19	177	301	23	182	458	28	180	617	36	190	



